

PRODUCT INFORMATION

NAME	Typhoon 3™
MODEL NUMBER	FZVAAK-3
MSRP	\$337.49
UPC / BARCODE	850020839629



PRODUCT IMAGE



DESCRIPTION

Now introducing the 4-Gallon Typhoon Series 3 Sprayer! With a 30-ft spray distance, this sprayer introduces design updates that significantly improve your spraying experience. By taking our customers feedback, we've implemented various tank advancements and brand new nozzle lineups.

To view the most updated operation guide visit: www.fzspray.com/operation-guides or scan the QR code



WHAT'S INCLUDED

	PART NUMBER	PART NUMBER
18V/5.2 Ah LI-ION BATTERY	FZAAEM	UV-RESISTANT 5-FT PVC HOSE
21V/2.5A BATTERY CHARGER	FZAAEL	FZRAOF
STAINLESS-STEEL WAND	FZRAAS	ADJUSTABLE CONE NOZZLE
SPRAY GUN	FZRABV	FZAA0L
COMFORTSTRAPS™	FZAAGD	0° PIN STREAM TEEJET NOZZLE
		FZAA0K
		45° FAN TEEJET NOZZLE
		FZAA0M

LOGISTICAL INFORMATION

GROSS / NET WEIGHT	16 / 14 pounds	PALLET QUANTITY	36 units
PACKAGE SIZE	14" x 9.5" x 21.7"	20' GP QUANTITY	420 units
WEIGHT PER UNIT	16 lbs	40' GP QUANTITY	840 units
WEIGHT PER PALLET	627 lbs	40' HQ QUANTITY	1080 units

PRODUCT SPECIFICATIONS

TANK TYPE	4-Gallon Backpack		GUN / WAND TYPE	Pressure Washer Spray Gun with Viton™ Seal / Quick-Connect Stainless Steel Wand	
PUMP TYPE	High Pressure Diaphragm Pump (LR)		BATTERY VOLTAGE/CAPACITY	18V / 5.2Ah	
WORKING PRESSURE	Low Speed (open flow) 8 psi	High Speed (dead head) 115 psi	BATTERY CELL TYPE	Lithium Ion	
SEAL TYPE	Viton™		CHARGER TYPE	21V / 2.5A	
FLOW RATE	Low Speed (open flow) .42 GPM	High Speed (open flow) 1.12 GPM	CHARGE TIME	~2 hours	
LIQUID OUTPUT / CHARGE	Low Speed (open flow) > 110 gal	High Speed (open flow) > 110 gal	BATTERY CYCLE LIFE	1,000 Charge Cycles	
SPRAY DISTANCE	> 30 Feet (10 Meters)		CONTINUOUS WORKING TIME	Low Speed > 180 minutes	High Speed > 120 minutes
			AGENCY/STANDARDS APPROVALS	UL / CE / RoHS	