

PRODUCT INFORMATION

NAME	Storm™ 2-Gallon
MODEL NUMBER	FZVAQP
MSRP	\$281.24
UPC / BARCODE	850037716296



PRODUCT IMAGE



DESCRIPTION

The STORM 2GAL features SwapTank™ technology, allowing applicators to bring extra, prefilled tanks on-site to increase spray capacity and quickly switch between chemicals. This sprayer allows for both high and low output capability. Applicators can spray anywhere between 0.05 to 1.10 gallons per minute with any nozzle tip.

To view the most updated operation guide visit: www.fzspray.com/operation-guides or scan the QR code



WHAT'S INCLUDED

	PART NUMBER	PART NUMBER
18V/5.2 Ah LI-ION BATTERY	FZAAEM	2-GALLON SWAPTANK™
21V/2.5A BATTERY CHARGER	FZAAEL	ADJUSTABLE CONE NOZZLE
WAND, GUN & HOSE ASSEMBLY	FZRAQX-V4	0° PIN STREAM TEEJET NOZZLE
BASE ASSEMBLY	FZRARU	45° FAN TEEJET NOZZLE
COMFORTSTRAPS™	FZAASG	

LOGISTICAL INFORMATION

GROSS / NET WEIGHT	14.5 / 12 pounds	PALLET QUANTITY	60 units
PACKAGE SIZE	26" x 12" x 9"	20' GP QUANTITY	420 units
WEIGHT PER UNIT	14.5 lbs	40' GP QUANTITY	840 units
WEIGHT PER PALLET	870 lbs	40' HQ QUANTITY	1080 units

PRODUCT SPECIFICATIONS

TANK TYPE	2-Gallon Backpack		GUN / WAND TYPE	Inline Spray Gun / Stainless Steel Wand with 45° Bend	
PUMP TYPE	High Pressure Recirculating Diaphragm (LR)		BATTERY VOLTAGE/CAPACITY	18V / 5.2Ah	
WORKING PRESSURE	Low Speed (open flow) 8 psi	High Speed (dead head) 115 psi	BATTERY CELL TYPE	Lithium-ion	
SEAL TYPE	Viton™		CHARGER TYPE	21V / 2.5A	
FLOW RATE	Low Speed (open flow) .05 GPM	High Speed (open flow) 1.10 GPM	CHARGE TIME	~2 hours	
LIQUID OUTPUT / CHARGE	Low Speed (open flow) > 110 gal	High Speed (open flow) > 110 gal	BATTERY CYCLE LIFE	1,000 Charge Cycles	
SPRAY DISTANCE	> 30 Feet (10 Meters)		CONTINUOUS WORKING TIME	Low Speed > 180 minutes	High Speed > 120 minutes
			AGENCY/STANDARDS APPROVALS	UL / CE / RoHS	